

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 September 2010 (10.09.2010)

PCT

(10) International Publication Number
WO 2010/100454 A1

(51) International Patent Classification:
F04D 25/08 (2006.01) *F04F 5/46* (2006.01)
F04F 5/16 (2006.01)

(21) International Application Number:
PCT/GB2010/050273

(22) International Filing Date:
18 February 2010 (18.02.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0903666.6 4 March 2009 (04.03.2009) GB
0903667.4 4 March 2009 (04.03.2009) GB
0903675.7 4 March 2009 (04.03.2009) GB

(71) Applicant (for all designated States except US): **DYSON TECHNOLOGY LIMITED** [GB/GB]; Tetbury Hill, Malmesbury Wiltshire SN16 0RP (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GAMMACK, Peter** [GB/GB]; Dyson Technology Limited, Tetbury Hill, Malmesbury Wiltshire SN16 0RP (GB).

(74) Agents: **BOOTH, Andrew** et al.; Dyson Technology Limited, Intellectual Property Department, Tetbury Hill, Malmesbury, Wiltshire SN16 0RP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: A FAN




FIG. 2

(57) Abstract: A fan assembly for creating an air current comprises a base (12) having an air inlet (20) and an air outlet (88), the base housing an impeller (64) and a motor (68) for rotating the impeller to create an air flow passing from the air inlet to the air outlet. The fan assembly further comprises a vertically oriented, elongate annular nozzle (14) comprising an interior passage (94) having an air inlet (102) for receiving the air flow from the base, and a mouth (26) for emitting the air flow, the nozzle defining an opening (24) through which air from outside the fan assembly is drawn by the air flow emitted from the mouth.



WO 2010/100454 A1

A Fan

The present invention relates to a fan assembly. In a preferred embodiment, the present invention relates to a domestic fan, such as a tower fan, for creating an air current, for
5 example in a room, office or other domestic environment.

A conventional domestic fan typically includes a set of blades or vanes mounted for rotation about an axis, and drive apparatus for rotating the set of blades to generate an air flow. The movement and circulation of the air flow creates a 'wind chill' or breeze
10 and, as a result, the user experiences a cooling effect as heat is dissipated through convection and evaporation.

Such fans are available in a variety of sizes and shapes. For example, a ceiling fan can be at least 1 m in diameter, and is usually mounted in a suspended manner from the
15 ceiling to provide a downward flow of air to cool a room. On the other hand, desk fans are often around 30 cm in diameter, and are usually free standing and portable. Floor-standing tower fans generally comprise an elongate, vertically extending casing around 1 m high and housing one or more sets of rotary blades for generating an air flow, usually in the range from 300 to 500 l/s. An oscillating mechanism may be employed to
20 rotate the outlet from the tower fan so that the air flow is swept over a wide area of a room.

A disadvantage of this type of arrangement is that the air flow produced by the rotating blades of the fan is generally not uniform. This is due to variations across the blade
25 surface or across the outward facing surface of the fan. The extent of these variations can vary from product to product and even from one individual fan machine to another. These variations result in the generation of an uneven or 'choppy' air flow which can be felt as a series of pulses of air and which can be uncomfortable for a user.

30 In a domestic environment it is desirable for appliances to be as small and compact as possible due to space restrictions. It is undesirable for parts of the appliance to project

outwardly, or for a user to be able to touch any moving parts, such as the blades. Many fans tend to have safety features such as a cage or shroud around the blades to prevent injury from the moving parts of the fan, but such caged parts can be difficult to clean.

- 5 The present invention seeks to provide an improved fan assembly which obviates disadvantages of the prior art.

In a first aspect the present invention provides a fan assembly for creating an air current, the fan assembly comprising a base having an air inlet and an air outlet, the base
10 housing an impeller and a motor for rotating the impeller to create an air flow passing from the air inlet to the air outlet, and a vertically oriented, elongate annular nozzle comprising an interior passage for receiving the air flow from the base and a mouth for emitting the air flow, the nozzle defining an opening through which air from outside the fan assembly is drawn by the air flow emitted from the mouth.

15

With this fan assembly an air current can be generated and a cooling effect created without the use of a bladed fan. The air current created by the fan assembly has the benefit of being an air flow with low turbulence and with a more linear air flow profile than that provided by other prior art devices. This can improve the comfort of a user
20 receiving the air flow.

In the following description of fan assemblies, and, in particular a fan of the preferred embodiment, the term 'bladeless' is used to describe a fan assembly in which air flow is emitted or projected forward from the fan assembly without the use of moving blades.
25 By this definition a bladeless fan assembly can be considered to have an output area or emission zone absent moving blades from which the air flow is directed towards a user or into a room. The output area of the bladeless fan assembly may be supplied with a primary air flow generated by one of a variety of different sources, such as pumps, generators, motors or other fluid transfer devices, and which may include a rotating
30 device such as a motor rotor and/or a bladed impeller for generating the air flow. The generated primary air flow can pass from the room space or other environment outside

the fan assembly through the interior passage to the nozzle, and then back out to the room space through the mouth of the nozzle.

5 Hence, the description of a fan assembly as bladeless is not intended to extend to the description of the power source and components such as motors that are required for secondary fan functions. Examples of secondary fan functions can include lighting, adjustment and oscillation of the fan assembly.

10 The direction in which air is emitted from the mouth is preferably substantially at a right angle to the direction in which the air flow passes through at least part of the interior passage. In the preferred embodiment, the air flow passes through at least part of the interior passage in a substantially vertical direction, and the air is emitted from the mouth in a substantially horizontal direction. The interior passage is preferably located towards the front of the nozzle, whereas the mouth is preferably located towards the rear of the nozzle and arranged to direct air towards the front of the nozzle and through the opening. Consequently, in the preferred embodiment the mouth is shaped so as substantially to reverse the flow direction of each portion of the air flow as it passes from the interior passage to an outlet of the mouth. The mouth is preferably substantially U-shaped in cross-section, and preferably narrows towards the outlet thereof.

25 The shape of the nozzle is not constrained by the requirement to include space for a bladed fan. Preferably, the interior passage surrounds the opening. For example, the interior passage may extend about the opening by a distance in the range from 50 to 250 cm. In a preferred embodiment the nozzle is an elongate, annular nozzle which preferably has a height in the range from 500 to 1000 mm, and a width in the range from 100 to 300 mm. The nozzle is preferably shaped to receive the air flow at one end thereof and to divide the air flow into two air streams, preferably with each air stream flowing along a respective elongate side of the opening.

30

The nozzle preferably comprises an annular inner casing section and an annular outer casing section which define the interior passage, the mouth and the opening. Each casing section may comprise a plurality of components, but in the preferred embodiment each of these sections is formed from a single annular component. The
5 outer casing section is preferably shaped so as to partially overlap the inner casing section to define at least one outlet of the mouth between overlapping portions of the external surface of the inner casing section and the internal surface of the outer casing section of the nozzle. Each outlet is preferably in the form of a slot, preferably having a width in the range from 0.5 to 5 mm. In the preferred embodiment, the mouth
10 comprises a plurality of such outlets spaced about the opening. For example, one or more sealing members may be located within the mouth to define a plurality of spaced apart outlets. Preferably, the outlets are of substantially the same size. In the preferred embodiment in which the nozzle is in the form of an annular, elongate nozzle, each outlet is preferably located along a respective elongate side of the inner periphery of the
15 nozzle.

The nozzle may comprise a plurality of spacers for urging apart the overlapping portions of the inner casing section and the outer casing section of the nozzle. This can enable a substantially uniform outlet width to be achieved about the opening. The
20 uniformity of the outlet width results in a relatively smooth, substantially even output of air from the nozzle.

The nozzle may comprise a surface, preferably a Coanda surface, located adjacent the mouth and over which the mouth is arranged to direct the air flow emitted therefrom. In
25 the preferred embodiment, the external surface of the inner casing section of the nozzle is shaped to define the Coanda surface. A Coanda surface is a known type of surface over which fluid flow exiting an output orifice close to the surface exhibits the Coanda effect. The fluid tends to flow over the surface closely, almost 'clinging to' or 'hugging' the surface. The Coanda effect is already a proven, well documented method of
30 entrainment in which a primary air flow is directed over a Coanda surface. A description of the features of a Coanda surface, and the effect of fluid flow over a

Coanda surface, can be found in articles such as Reba, Scientific American, Volume 214, June 1966 pages 84 to 92. Through use of a Coanda surface, an increased amount of air from outside the fan assembly is drawn through the opening by the air emitted from the mouth.

5

In the preferred embodiment an air flow is created through the nozzle of the fan assembly. In the following description this air flow will be referred to as primary air flow. The primary air flow is emitted from the mouth of the nozzle and preferably passes over a Coanda surface. The primary air flow entrains air surrounding the mouth
10 of the nozzle, which acts as an air amplifier to supply both the primary air flow and the entrained air to the user. The entrained air will be referred to here as a secondary air flow. The secondary air flow is drawn from the room space, region or external environment surrounding the mouth of the nozzle and, by displacement, from other regions around the fan assembly, and passes predominantly through the opening defined
15 by the nozzle. The primary air flow directed over the Coanda surface combined with the entrained secondary air flow equates to a total air flow emitted or projected forward from the opening defined by the nozzle. The total air flow is sufficient for the fan assembly to create an air current suitable for cooling. Preferably, the entrainment of air surrounding the mouth of the nozzle is such that the primary air flow is amplified by at
20 least five times, more preferably by at least ten times, while a smooth overall output is maintained. Preferably, the nozzle comprises a diffuser located downstream of the Coanda surface. The diffuser directs the air flow emitted towards a user's location while maintaining a smooth, even output, generating a suitable cooling effect without the user feeling a 'choppy' flow.

25

Preferably, the nozzle comprises a plurality of stationary guide vanes located within the interior passage and each for directing a portion of the air flow towards the mouth. The use of such guide vanes can assist in producing a substantially uniform distribution of the air flow through the mouth.

30

The motor preferably comprises a DC brushless motor. This can avoid frictional losses and carbon debris from the brushes used in a traditional brushed motor. Reducing carbon debris and emissions is advantageous in a clean or pollutant sensitive environment such as a hospital or around those with allergies. While induction motors, which are generally used in bladed fans, also have no brushes, a DC brushless motor can provide a much wider range of operating speeds than an induction motor. The impeller is preferably a mixed flow impeller.

The air inlet of the base may comprise a grille comprising an array of apertures. The air outlet of the base is preferably arranged to convey the air flow in a substantially vertical direction into the nozzle. The base is preferably cylindrical in shape, and preferably has a height in the range from 100 to 300 mm. The fan assembly preferably has a height in the range from 600 to 1500 mm.

The fan assembly may be desk, table or floor standing, or wall or ceiling mountable. For example, the fan assembly may be a portable, floor standing tower fan for creating an air current for circulating air, for example in a room, office or other domestic environment.

In a second aspect the present invention provides a portable tower fan comprising a base having an air inlet and an air outlet, the base housing an impeller and a motor for rotating the impeller to create an air flow passing from the air inlet to the air outlet, and a vertically oriented, elongate annular casing comprising an interior passage for receiving the air flow from the base, and a mouth for emitting the air flow, the casing defining an opening through which air from outside the fan assembly is drawn by the air flow emitted from the mouth.

In a third aspect the present invention provides a portable tower fan comprising an impeller located within an impeller housing, a motor for rotating the impeller to create an air flow which is exhausted from the impeller housing in a substantially vertical direction, and a vertically oriented, elongate casing comprising an interior passage for

receiving the air flow and a mouth shaped to emit the air flow. Preferably, the air flow is emitted from the mouth in a substantially horizontal direction. The casing preferably comprises an opening through which air from outside the fan is drawn by the air flow emitted from the mouth. The interior passage is preferably shaped to divide the air flow into two air streams and to direct each air stream along a respective side of the opening. The casing is preferably annular, and may comprise an annular inner casing section and an annular outer casing section which together define the interior passage and the mouth. The impeller housing is preferably located within a base of the fan, the base comprising an air inlet through which air is drawn into the base with rotation of the impeller.

In a fourth aspect the present invention provides a fan assembly for creating an air current, the fan assembly comprising a base having an air inlet and an air outlet, the base housing an impeller and a motor for rotating the impeller to create an air flow passing from the air inlet to the air outlet, and an annular nozzle mounted on the base, the nozzle comprising an interior passage for receiving the air flow from the base and a mouth for emitting the air flow, the nozzle defining an opening through which air from outside the fan assembly is drawn by the air flow emitted from the mouth, the nozzle having a height which is at least 60%, preferably at least 70%, of the height of the fan assembly. The nozzle is preferably a vertically oriented, elongate annular nozzle. The base preferably has a height in the range from 100 to 300 mm, and the nozzle preferably has a height in the range from 500 to 1000 mm.

Features of the first aspect of the invention are equally applicable to any of the second to fourth aspects of the invention, and vice versa.

An embodiment of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a front view of a tower fan;

Figure 2 is a perspective view of the fan of Figure 1;

Figure 3 is a cross-sectional view of the base of the fan of Figure 1;

5 Figure 4 is an exploded view of the nozzle of the fan of Figure 1;

Figure 5 is an enlarged view of area A indicated in Figure 4;

Figure 6 is a front view of the nozzle of Figure 4;

10

Figure 7 is a sectional view of the nozzle taken along line E-E in Figure 6;

Figure 8 is a sectional view of the nozzle taken along line D-D in Figure 6;

15 Figure 9 is an enlarged view of a section of the nozzle illustrated in Figure 8;

Figure 10 is a sectional view of the nozzle taken along line C-C in Figure 6;

Figure 11 is an enlarged view of a section of the nozzle illustrated in Figure 10;

20

Figure 12 is a sectional view of the nozzle taken along line B-B in Figure 6;

Figure 13 is an enlarged view of a section of the nozzle illustrated in Figure 12; and

25 Figure 14 illustrates the air flow through part of the nozzle of the fan of Figure 1.

Figures 1 and 2 illustrate an embodiment of a bladeless fan assembly. In this embodiment, the bladeless fan assembly is in the form of a domestic, portable tower fan 10 comprising a base 12 and an air outlet in the form of a nozzle 14 mounted on and supported by the base 12. The base 12 comprises a substantially cylindrical outer casing 16 mounted optionally on a disc-shaped base plate 18. The outer casing 16

30

comprises a plurality of air inlets 20 in the form of apertures formed in the outer casing 16 and through which a primary air flow is drawn into the base 12 from the external environment. The base 12 further comprises a plurality of user-operable buttons 21 and a user-operable dial 22 for controlling the operation of the fan 10. In this embodiment
5 the base 12 has a height in the range from 100 to 300 mm, and the outer casing 16 has a diameter in the range from 100 to 200 mm.

The nozzle 14 has an elongate, annular shape and defines a central elongate opening 24. The nozzle 14 has a height in the range from 500 to 1200 mm, and a width in the range
10 from 150 to 400 mm. In this example, the height of the nozzle is around 750 mm and the width of the nozzle is around 190 mm. The nozzle 14 comprises a mouth 26 located towards the rear of the fan 10 for emitting air from the fan 10 and through the opening 24. The mouth 26 extends at least partially about the opening 24. The inner periphery of the nozzle 14 comprises a Coanda surface 28 located adjacent the mouth 26 and over
15 which the mouth 26 directs the air emitted from the fan 10, a diffuser surface 30 located downstream of the Coanda surface 28 and a guide surface 32 located downstream of the diffuser surface 30. The diffuser surface 30 is arranged to taper away from the central axis X of the opening 24 in such a way so as to assist the flow of air emitted from the fan 10. The angle subtended between the diffuser surface 30 and the central axis X of
20 the opening 24 is in the range from 5 to 15°, and in this embodiment is around 7°. The guide surface 32 is arranged at an angle to the diffuser surface 30 to further assist the efficient delivery of a cooling air flow from the fan 10. In the illustrated embodiment the guide surface 32 is arranged substantially parallel to the central axis X of the opening 24 to present a substantially flat and substantially smooth face to the air flow
25 emitted from the mouth 26. A visually appealing tapered surface 34 is located downstream from the guide surface 32, terminating at a tip surface 36 lying substantially perpendicular to the central axis X of the opening 24. The angle subtended between the tapered surface 34 and the central axis X of the opening 24 is preferably around 45°. The overall depth of the nozzle 24 in a direction extending along the
30 central axis X of the opening 24 is in the range from 100 to 150 mm, and in this example is around 110 mm.

Figure 3 illustrates a sectional view through the base 12 of the fan 10. The outer casing 16 of the base 12 comprises a lower casing section 40 and a main casing section 42 mounted on the lower casing section 40. The lower casing section 40 houses a controller, indicated generally at 44, for controlling the operation of the fan 10 in response to depression of the user operable buttons 21 shown in Figures 1 and 2, and/or manipulation of the user operable dial 22. The lower casing section 40 may optionally comprise a sensor 46 for receiving control signals from a remote control (not shown), and for conveying these control signals to the controller 44. These control signals are preferably infrared signals. The sensor 46 is located behind a window 47 through which the control signals enter the lower casing section 40 of the outer casing 16 of the base 12. A light emitting diode (not shown) may be provided for indicating whether the fan 10 is in a stand-by mode. The lower casing section 40 also houses a mechanism, indicated generally at 48, for oscillating the main casing section 42 relative to the lower casing section 40. The range of each oscillation cycle of the main casing section 42 relative to the lower casing section 40 is preferably between 60° and 120°, and in this embodiment is around 90°. In this embodiment, the oscillating mechanism 48 is arranged to perform around 3 to 5 oscillation cycles per minute. A mains power cable 50 extends through an aperture formed in the lower casing section 40 for supplying electrical power to the fan 10.

The main casing section 42 comprises a cylindrical grille 60 in which an array of apertures 62 is formed to provide the air inlets 20 of the outer casing 16 of the base 12. The main casing section 42 houses an impeller 64 for drawing the primary air flow through the apertures 62 and into the base 12. Preferably, the impeller 64 is in the form of a mixed flow impeller. The impeller 64 is connected to a rotary shaft 66 extending outwardly from a motor 68. In this embodiment, the motor 68 is a DC brushless motor having a speed which is variable by the controller 44 in response to user manipulation of the dial 22 and/or a signal received from the remote control. The maximum speed of the motor 68 is preferably in the range from 5,000 to 10,000 rpm. The motor 68 is housed within a motor bucket comprising an upper portion 70 connected to a lower

portion 72. The upper portion 70 of the motor bucket comprises a diffuser 74 in the form of a stationary disc having spiral blades. The motor bucket is located within, and mounted on, a generally frusto-conical impeller housing 76 connected to the main casing section 42. The impeller 42 and the impeller housing 76 are shaped so that the impeller 42 is in close proximity to, but does not contact, the inner surface of the impeller housing 76. A substantially annular inlet member 78 is connected to the bottom of the impeller housing 76 for guiding the primary air flow into the impeller housing 76. The impeller housing 76 is oriented so that the primary air flow is exhausted from the impeller housing 76 in a substantially vertical direction.

10

A profiled upper casing section 80 is connected to the open upper end of the main casing section 42 of the base 12, for example by means of snap-fit connections. An O-ring sealing member may be used to form an air-tight seal between the main casing section 42 and the upper casing section 80 of the base 12. The upper casing section 80 comprises a chamber 86 for receiving the primary air flow from the main casing section 42, and an aperture 88 through which the primary air flow passes from the base 12 into the nozzle 14.

15

Preferably, the base 12 further comprises silencing foam for reducing noise emissions from the base 12. In this embodiment, the main casing section 42 of the base 12 comprises a first, generally cylindrical foam member 89a located beneath the grille 60, and a second, substantially annular foam member 89b located between the impeller housing 76 and the inlet member 78.

20

The nozzle 14 of the fan 10 will now be described with reference to Figures 4 to 13. The nozzle 14 comprises a casing comprising an elongate, annular outer casing section 90 connected to and extending about an elongate, annular inner casing section 92. The inner casing section 92 defines the central opening 24 of the nozzle 14, and has an external peripheral surface 93 which is shaped to define the Coanda surface 28, diffuser surface 30, guide surface 32 and tapered surface 34.

25

30

The outer casing section 90 and the inner casing section 92 together define an annular interior passage 94 of the nozzle 14. The interior passage 94 is located towards the front of the fan 10. The interior passage 94 extends about the opening 24, and thus comprises two substantially vertically extending sections each adjacent a respective elongate side of the central opening 24, an upper curved section joining the upper ends of the vertically extending sections, and a lower curved section joining the lower ends of the vertically extending sections. The interior passage 94 is bounded by the internal peripheral surface 96 of the outer casing section 90 and the internal peripheral surface 98 of the inner casing section 92. The outer casing section 90 comprises a base 100 which is connected to, and over, the upper casing section 80 of the base 12, for example by a snap-fit connection. The base 100 of the outer casing section 90 comprises an aperture 102 which is aligned with the aperture 88 of the upper casing section 80 of the base 12 and through which the primary air flow enters the lower curved portion of the interior passage 94 of the nozzle 14 from the base 12 of the fan 10.

With particular reference to Figures 8 and 9, the mouth 26 of the nozzle 14 is located towards the rear of the fan 10. The mouth 26 is defined by overlapping, or facing, portions 104, 106 of the internal peripheral surface 96 of the outer casing section 90 and the external peripheral surface 93 of the inner casing section 92, respectively. In this embodiment, the mouth 26 comprises two sections each extending along a respective elongate side of the central opening 24 of the nozzle 14, and in fluid communication with a respective vertically extending section of the interior passage 94 of the nozzle 14. The air flow through each section of the mouth 26 is substantially orthogonal to the air flow through the respective vertically extending portion of the interior passage 94 of the nozzle 14. Each section of the mouth 26 is substantially U-shaped in cross-section, and so as a result the direction of the air flow is substantially reversed as the air flow passes through the mouth 26. In this embodiment, the overlapping portions 104, 106 of the internal peripheral surface 96 of the outer casing section 90 and the external peripheral surface 93 of the inner casing section 92 are shaped so that each section of the mouth 26 comprises a tapering portion 108 narrowing to an outlet 110. Each outlet 110 is in the form of a substantially vertically extending slot, preferably having a relatively constant

width in the range from 0.5 to 5 mm. In this embodiment each outlet 110 has a width of around 1 mm.

The mouth 26 may thus be considered to comprise two outlets 110 each located on a
5 respective side of the central opening 24. Returning to Figure 4, the nozzle 14 further comprises two curved seal members 112, 114 each for forming a seal between the outer casing section 90 and the inner casing section 92 so that there is substantially no leakage of air from the curved sections of the interior passage 94 of the nozzle 14.

10 In order to direct the primary air flow into the mouth 26, the nozzle 14 comprises a plurality of stationary guide vanes 120 located within the interior passage 94 and each for directing a portion of the air flow towards the mouth 26. The guide vanes 120 are illustrated in Figures 4, 5, 7, 10 and 11. The guide vanes 120 are preferably integral with the internal peripheral surface 98 of the inner casing section 92 of the nozzle 14.
15 The guide vanes 120 are curved so that there is no significant loss in the velocity of the air flow as it is directed into the mouth 26. In this embodiment the nozzle 14 comprises two sets of guide vanes 120, with each set of guide vanes 120 directing air passing along a respective vertically extending portion of the interior passage 94 towards its associated section of the mouth 26. Within each set, the guide vanes 120 are
20 substantially vertically aligned and evenly spaced apart to define a plurality of passageways 122 between the guide vanes 120 and through which air is directed into the mouth 26. The even spacing of the guide vanes 120 provides a substantially even distribution of the air stream along the length of the section of the mouth 26.

25 With reference to Figure 11, the guide vanes 120 are preferably shaped so that a portion 124 of each guide vane 120 engages the internal peripheral surface 96 of the outer casing section 90 of the nozzle 24 so as to urge apart the overlapping portions 104, 106 of the internal peripheral surface 96 of the outer casing section 90 and the external peripheral surface 93 of the inner casing section 92. This can assist in maintaining the
30 width of each outlet 110 at a substantially constant level along the length of each section of the mouth 26. With reference to Figures 7, 12 and 13, in this embodiment additional

spacers 126 are provided along the length of each section of the mouth 26, also for urging apart the overlapping portions 104, 106 of the internal peripheral surface 96 of the outer casing section 90 and the external peripheral surface 93 of the inner casing section 92, to maintain the width of the outlet 110 at the desired level. Each spacer 126 is located substantially midway between two adjacent guide vanes 120. To facilitate manufacture the spacers 126 are preferably integral with the external peripheral surface 98 of the inner casing section 92 of the nozzle 14. Additional spacers 126 may be provided between adjacent guide vanes 120 if so desired.

10 In use, when the user depresses an appropriate one of the buttons 21 on the base 12 of the fan 10 the controller 44 activates the motor 68 to rotate the impeller 64, which causes a primary air flow to be drawn into the base 12 of the fan 10 through the air inlets 20. The primary air flow may be up to 30 litres per second, more preferably up to 50 litres per second. The primary air flow passes through the impeller housing 76 and the upper casing section 80 of the base 12, and enters the base 100 of the outer casing section 90 of the nozzle 14, from which the primary air flow enters the interior passage 94 of the nozzle 14.

With reference also to Figure 14 the primary air flow, indicated at 148, is divided into two air streams, one of which is indicated at 150 in Figure 14, which pass in opposite directions around the central opening 24 of the nozzle 14. Each air stream 150 enters a respective one of the two vertically extending sections of the interior passage 94 of the nozzle 14, and is conveyed in a substantially vertical direction up through each of these sections of the interior passage 94. The set of guide vanes 120 located within each of these sections of the interior passage 94 directs the air stream 150 towards the section of the mouth 26 located adjacent that vertically extending section of the interior passage 94. Each of the guide vanes 120 directs a respective portion 152 of the air stream 150 towards the section of the mouth 26 so that there is a substantially uniform distribution of the air stream 150 along the length of the section of the mouth 26. The guide vanes 120 are shaped so that each portion 152 of the air stream 150 enters the mouth 26 in a substantially horizontal direction. Within each section of the mouth 26, the flow

direction of the portion of the air stream is substantially reversed, as indicated at 154 in Figure 14. The portion of the air stream is constricted as the section of the mouth 26 tapers towards the outlet 110 thereof, channeled around the spacer 126 and emitted through the outlet 110, again in a substantially horizontal direction.

5

The primary air flow emitted from the mouth 26 is directed over the Coanda surface 28 of the nozzle 14, causing a secondary air flow to be generated by the entrainment of air from the external environment, specifically from the region around the outlets 110 of the mouth 26 and from around the rear of the nozzle 14. This secondary air flow passes
10 predominantly through the central opening 24 of the nozzle 14, where it combines with the primary air flow to produce a total air flow 156, or air current, projected forward from the nozzle 14.

The even distribution of the primary air flow along the mouth 26 of the nozzle 14
15 ensures that the air flow passes evenly over the diffuser surface 30. The diffuser surface 30 causes the mean speed of the air flow to be reduced by moving the air flow through a region of controlled expansion. The relatively shallow angle of the diffuser surface 30 to the central axis X of the opening 24 allows the expansion of the air flow to occur gradually. A harsh or rapid divergence would otherwise cause the air flow to become
20 disrupted, generating vortices in the expansion region. Such vortices can lead to an increase in turbulence and associated noise in the air flow, which can be undesirable, particularly in a domestic product such as a fan. In the absence of the guide vanes 120 most of the primary air flow would tend to leave the fan 10 through the upper part of the mouth 26, and to leave the mouth 26 upwardly at an acute angle to the central axis of
25 the opening 24. As a result there would be an uneven distribution of air within the air current generated by the fan 10. Furthermore, most of the air flow from the fan 10 would not be properly diffused by the diffuser surface 30, leading to the generation of an air current with much greater turbulence.

30 The air flow projected forwards beyond the diffuser surface 30 can tend to continue to diverge. The presence of the guide surface 32 extending substantially parallel to the

central axis X of the opening 30 tends to focus the air flow towards the user or into a room.

Depending on the speed of the motor 64, the mass flow rate of the air current projected forward from the fan 10 may be up to 500 litres per second, and in the preferred embodiment is up to 700 litres per second, and the maximum speed of the air current may be in the range from 3 to 4 m/s.

The invention is not limited to the detailed description given above. Variations will be apparent to the person skilled in the art.

For example, the base and the nozzle of the fan may be of a different shape and/or shape. The outlet of the mouth may be modified. For example, the outlet of the mouth may be widened or narrowed to a variety of spacings to maximise air flow. The air flow emitted from the mouth may pass over a surface, such as a Coanda surface, but alternatively the air flow may be emitted through the mouth and projected forward from the fan without passing over an adjacent surface. The Coanda effect may be effected over a number of different surfaces, or a number of internal or external designs may be used in combination to achieve the flow and entrainment required. The diffuser surface may be comprised of a variety of diffuser lengths and structures. The guide surface may be a variety of lengths, and may be arranged at a number of different positions and orientations as required for different fan requirements and different types of fan performance. Additional features such as lighting or a clock or LCD display may be provided within the central opening defined by the nozzle.

25

CLAIMS

1. A fan assembly for creating an air current, the fan assembly comprising a base
5 having an air inlet and an air outlet, the base housing an impeller and a motor for rotating the impeller to create an air flow passing from the air inlet to the air outlet, and a vertically oriented, elongate annular nozzle comprising an interior passage for receiving the air flow from the base and a mouth for emitting the air flow, the nozzle defining an opening through which air from outside the fan assembly is drawn by the air
10 flow emitted from the mouth.
2. A fan assembly as claimed in claim 1, wherein the interior passage is shaped to divide the air flow into two air streams and to direct each air stream along a respective side of the opening.
15
3. A fan assembly as claimed in claim 1 or claim 2, wherein the nozzle comprises an annular inner casing section and an annular outer casing section which together define the interior passage and the mouth.
- 20 4. A fan assembly as claimed in claim 3, wherein the mouth comprises an outlet located between an external surface of the inner casing section of the nozzle and an internal surface of the outer casing section of the nozzle.
5. A fan assembly as claimed in claim 4, wherein the outlet is in the form of a slot.
25
6. A fan assembly as claimed in claim 4 or claim 5, wherein the outlet has a width in the range from 0.5 to 5 mm.
7. A fan assembly as claimed in any of claims 4 to 6, wherein the mouth comprises
30 a plurality of said outlets spaced about the opening.

8. A fan assembly as claimed in claim 7, wherein each of the outlets is substantially vertically oriented.
9. A fan assembly as claimed in claim 8, wherein the outlets are of substantially the same size.
10. A fan assembly as claimed in any of the preceding claims, wherein the interior passage extends about the opening by a distance in the range from 500 to 2500 mm.
- 10 11. A fan assembly as claimed in any of the preceding claims, wherein the nozzle comprises a surface located adjacent the mouth and over which the mouth is arranged to direct the air flow.
12. A fan assembly as claimed in claim 11, wherein the surface is a Coanda surface.
- 15 13. A fan assembly as claimed in claim 11 or claim 12, wherein the nozzle comprises a diffuser located downstream of the Coanda surface.
14. A fan assembly as claimed in any of the preceding claims, wherein the air inlet of the base comprises a grille comprising an array of apertures.
- 20 15. A fan assembly as claimed in any of the preceding claims, wherein the air outlet of the base is arranged to convey the air flow in a substantially vertical direction into the nozzle.
- 25 16. A fan assembly as claimed in any of the preceding claims, wherein the base has a height in the range from 100 to 300 mm.
17. A fan assembly as claimed in any of the preceding claims, wherein the base is substantially cylindrical.
- 30

18. A fan assembly as claimed in any of the preceding claims, wherein the motor is a DC brushless motor.

19. A fan assembly as claimed in any of the preceding claims, wherein the fan
5 assembly has a height in the range from 600 to 1500 mm.

20. A fan assembly as claimed in any of the preceding claims, in the form of a portable tower fan.

10 21. A portable tower fan comprising a base having an air inlet and an air outlet, the base housing an impeller and a motor for rotating the impeller to create an air flow passing from the air inlet to the air outlet, and a vertically oriented, elongate annular casing comprising an interior passage for receiving the air flow from the base and a mouth for emitting the air flow, the casing defining an opening through which air from
15 outside the fan assembly is drawn by the air flow emitted from the mouth.

22. A fan as claimed in claim 21, wherein the interior passage is shaped to divide the air flow into two air streams and to direct each air stream along a respective side of the opening.

20

23. A fan as claimed in claim 21 or claim 22, wherein the casing comprises an annular inner casing section and an annular outer casing section which together define the interior passage and the mouth.

25 24. A fan as claimed in claim 23, wherein the mouth comprises an outlet located between an external surface of the inner casing section and an internal surface of the outer casing section.

25. A fan as claimed in claim 24, wherein the outlet is in the form of a slot.

30

26. A fan as claimed in claim 24 or claim 25, wherein the outlet has a width in the range from 0.5 to 5 mm.

27. A fan as claimed in any of claims 24 to 26, wherein the mouth comprises a plurality of said outlets spaced about the opening.

28. A fan as claimed in claim 27, wherein each of the outlets is substantially vertically oriented.

29. A fan as claimed in claim 28, wherein the outlets are of substantially the same size.

30. A fan as claimed in any of claims 21 to 29, wherein the interior passage extends about the opening by a distance in the range from 500 to 2500 mm.

31. A fan as claimed in any of claims 21 to 30, wherein the casing comprises a surface located adjacent the mouth and over which the mouth is arranged to direct the air flow.

32. A fan as claimed in claim 31, wherein the surface is a Coanda surface.

33. A fan as claimed in claim 31 or claim 32, wherein the casing comprises a diffuser located downstream of the Coanda surface.

34. A fan as claimed in any of claims 21 to 33, wherein the air inlet of the base comprises a grille comprising an array of apertures.

35. A fan as claimed in any of claims 21 to 34, wherein the air outlet of the base is arranged to convey the air flow in a substantially vertical direction into the casing.

36. A fan as claimed in any of claims 21 to 35, wherein the base has a height in the range from 100 to 300 mm.
37. A fan as claimed in any of claims 21 to 36, wherein the base is substantially
5 cylindrical.
38. A fan as claimed in any of claims 21 to 37, wherein the motor is a DC brushless motor.
- 10 39. A fan assembly or a fan substantially as hereinbefore described with reference to the accompanying drawings.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2010/050273

A. CLASSIFICATION OF SUBJECT MATTER
INV. F04D25/08 F04F5/16 F04F5/46
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
F04D F04F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 56 167897 A (TOKYO SHIBAURA ELECTRIC CO) 23 December 1981 (1981-12-23)	1, 2, 10, 11, 14-22, 30, 31, 34-39
Y	* abstract; figures 1,2	3, 4, 12, 13, 23, 24, 32, 33
X	US 2 488 467 A (DE LISIO SALVATORE) 15 November 1949 (1949-11-15) column 1, line 1 - line 9 column 1, line 18 - line 34; figures 1,2 ----- -/--	1, 2, 10, 11, 14-22, 30, 31, 34-36, 38, 39

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

29 June 2010

Date of mailing of the international search report

07/07/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Di Giorgio, F

INTERNATIONAL SEARCH REPORT

International application No

PCT/GB2010/050273

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 12 91 090 B (SCHMIDT GEB HALM ANNELIESE) 20 March 1969 (1969-03-20) column 2, line 7 - line 17 column 2, line 27 - line 52; figures 1,2 -----	1,2,11, 16-22, 31,36-39
X	US 5 881 685 A (FOSS JOHN F [US] ET AL) 16 March 1999 (1999-03-16)	39
Y	column 4, line 64 - column 5, line 19; figure 3	3,4,12, 13,23, 24,32,33
A	figure 13 -----	1
A	IMANTS REBA: "Applications of the Coanda effect" SCIENTIFIC AMERICAN, SCIENTIFIC AMERICAN INC., NEW YORK, NY, US, vol. 214, 1 June 1966 (1966-06-01), pages 84-92, XP009132496 ISSN: 0036-8733 cited in the application the whole document -----	12,13, 32,33
X,P	WO 2009/030879 A1 (DYSON TECHNOLOGY LTD [GB]; GAMMACK PETER DAVID [GB]; NICOLAS FREDERIC) 12 March 2009 (2009-03-12) page 13, line 28 - line 29 -----	1,21
X,P	WO 2009/030881 A1 (DYSON TECHNOLOGY LTD [GB]; GAMMACK PETER DAVID [GB]; NICOLAS FREDERIC) 12 March 2009 (2009-03-12) page 11, line 24 - line 25 -----	1,21

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/GB2010/050273

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 56167897	A	23-12-1981	NONE
US 2488467	A	15-11-1949	NONE
DE 1291090	B	20-03-1969	NONE
US 5881685	A	16-03-1999	AT 280896 T 15-11-2004 DE 69731337 D1 02-12-2004 EP 0820557 A1 28-01-1998 JP 11502586 T 02-03-1999 WO 9726450 A1 24-07-1997 US 5762034 A 09-06-1998
WO 2009030879	A1	12-03-2009	AU 2008294621 A1 12-03-2009 AU 2008294623 A1 12-03-2009 CA 2698489 A1 12-03-2009 CA 2698490 A1 12-03-2009 EP 2191142 A1 02-06-2010 GB 2452593 A 11-03-2009 WO 2009030881 A1 12-03-2009 JP 2009062986 A 26-03-2009 JP 2009062987 A 26-03-2009 US 2009060710 A1 05-03-2009 US 2009060711 A1 05-03-2009
WO 2009030881	A1	12-03-2009	AU 2008294621 A1 12-03-2009 AU 2008294623 A1 12-03-2009 CA 2698489 A1 12-03-2009 CA 2698490 A1 12-03-2009 EP 2191142 A1 02-06-2010 GB 2452593 A 11-03-2009 WO 2009030879 A1 12-03-2009 JP 2009062986 A 26-03-2009 JP 2009062987 A 26-03-2009 US 2009060710 A1 05-03-2009 US 2009060711 A1 05-03-2009